







Pos.	Matsushita		
	DA 12 SE		
1	14 1751		
2			
3	03 2035		
4			
5	16 2549		
6	05 8458		
7			
8	11 1567		
9			
10			
11			
12			

TECHNISCHE DATEN / TECHNICAL DATA / DONNEES TECHNIQUES						
Verdichter/Compressor/Compresseur		Matsushita				
Typ/Type		DA 12 SE				
Förderleistung/Delivery/Débit		l/h	2250			
Anlaufstrom/Starting current/Cour de démarrage		A	8,7			
Widerstand/Resistance/Résistance		Ha/main/prin	Ω	12,0		
		Hi/aux	Ω	28,7		
Temp.-Regler/Thermostat		Elektronisch				
Solltemperatur-Einstellung		°C	EIN	AUS		
		-18	-15	-16		
		-22	-19	-20		
		-26	-23	-24		
"alarm"			-9	-14		
Füllmenge/Fill.quantity/Charge		R600	siehe Typenschild			
Anschlußwert/Conn.load/Puiss. connectée		W	150			
Heizung/Heater/Chauffage						
Widerstand/Resistance/Résistance		Ω				
Leistung/Power/Puissance		W				
Ventilator/Blower/Ventilateur						
Widerstand/Resistance/Résistance		Ω				
Widerstand NTC-Fühler		°C	kΩ	°C	kΩ	°C
		-1	17,3	-15	36,5	-20
		-9	26,2	-16	38,8	-23
		-14	34,5	-19	45,9	-24
Magnetventil/Magnetic valve/Electrovanne						
Widerstand/Resistance/Résistance		Ω				
Spannung/Voltage/Tension		V				